



VACUUM TUMBLERS

40 to 800 lb. working capacity

- USDA approved
- All stainless steel construction
- 115 volt AC power
- Photoelectric safety shutoff
- Designed for easy operation and cleanup
- Variable speed control
- Tumble timer is standard on all units
- Built in vacuum system
- Made in the USA



LT-5 Tabletop Model Tumbler



LT-15 Floor Model Tumbler



LT-30 Floor Model Tumbler



LT-60 Large Capacity Tumbler



Vacuum Tumbled Products

Beef Brisket	Marinated Steaks	Boneless Hams	Pork Steaks
Beef Fajitas	Roast Beef	Picnic Hams	Chicken Breasts
Beef Jerky	Babyback Ribs	Pork Fajitas	Chicken Fajitas
Beef Ribs	Bacon	Pork Loins	BBQ Chicken
Corned Beef	Bone-in Hams	Pork Ribs	Buffalo Wings
Italian Beef			

Contact us at:

UltraSource LLC
1414 West 29th Street, Kansas City, MO 64108-3604 USA

800.777.5624

Telephone: 816.753.2150, Fax: 816.753.4976
info@UltraSourceUSA.com
UltraSourceUSA.com



UltraSource®

© Copyright 2013 UltraSource LLC

Think UltraSource First.



VACUUM TUMBLERS

Our Goals:

- Minimize curing or marinating time
- Improve product yields and profit
- Improve product quality and consistency
- Improve raw to finished goods time to market

Your Customers' Benefits:

- Product that is more tender, moist, and better tasting
- Improved product appearance and better color inside – more appetizing
- Consistent product quality with extended shelf life and fresher taste



LT-5



LT-15



LT-30



LT-60

UltraSource Vacuum Tumbler Specifications

MODEL		49 00 05 LT-5	49 00 15 LT-15	49 00 30 LT-30	49 00 60 LT-60
All stainless steel construction with USDA approval		Standard	Standard	Standard	Standard
Physical Dimensions					
Length		32-in.	47-in.	52-in.	76-in.
Width		20-in.	27-in.	31-in.	31-in.
Height		21-in.	35-in.	49-in.	49-in.
Working Capacity					
Pounds		40	150	400	800
Vacuum Pump System					
Maximum Vacuum (liquid trap)		26-in.	26-in.	26-in.	26-in.
Drum Speed					
Variable Speed Drive		1-20 rpm	1-9 rpm	1-9 rpm	1-9 rpm
Timer Controls		80 minutes	8-hour	8-hour	8-hour
Tumble Timer		Optional	Standard	Standard	Standard
Deluxe Control Panel	Maximums				
Delay Start	99 hrs./59 min.	N/A	Optional	Optional	Optional
Intermittent On	99 hrs./59 min.	N/A	Optional	Optional	Optional
Intermittent Off	99 hrs./59 min.	N/A	Optional	Optional	Optional
Total Time	99 hrs./59 min.	N/A	Optional	Optional	Optional
Electrical					
115 Volt, 60 Hertz, Single Phase					
Variable Speed Motor		1.8 amps	5.0 amps	6.2 amps	11.0 amps
Vacuum Pump Motor		2.0 amps	2.0 amps	9.4 amps	9.4 amps
Shipping Weight (Class 92.5)		100-lbs.	400-lbs.	650-lbs.	750-lbs.
Door Opening		-	12.5-in. x 23.75-in.	12.5-in. x 23.75-in.	12.5-in. x 23.75-in.



**Tumbler Lift Kit Option
for LT-30 and LT-60 only**

Popular Vacuum Tumbler Options

- Deluxe control panel with intermittent timer (49 00 32)
- Stainless steel lift kit raises LT-30 or LT-60 14-in. for easier unloading (49 00 33)
- Stainless steel cart to hold LT-5 tabletop tumbler (49 00 03)



UltraSource®