

## VACUUM TUMBLERS

- » USDA approved
- » All stainless steel construction
- » 115 volt AC power
- » Built in vacuum system
- » Photoelectric safety shutoff
- » Designed for easy operation and cleanup
- » Variable speed control
- » Made in the USA



**LT-5 Tabletop Model Tumbler**



**LT-15 Floor Model Tumbler**



**LT-30 Floor Model Tumbler**



**LT-60 Large Capacity Tumbler**

**40 to 800 lb. working capacity**  
**Popular Vacuum Tumbler Options:**

- » Deluxe control panel with intermittent timer (49 00 32)
- » Stainless steel lift kit raises LT-30 or LT-60 14-in. for easier unloading (49 00 33)
- » Stainless steel cart to hold LT-5 tabletop tumbler (49 00 03)



Beef Brisket	Marinated Steaks	Boneless Hams	Pork Steaks
Beef Fajitas	Roast Beef	Picnic Hams	Chicken Breasts
Beef Jerky	Babyback Ribs	Pork Fajitas	Chicken Fajitas
Beef Ribs	Bacon	Pork Loins	BBQ Chicken
Corned Beef	Bone-in Hams	Pork Ribs	Buffalo Wings
Italian Beef			

## VACUUM TUMBLERS

### Our Goals:

- » Minimize curing or marinating
- » Improve product yields and profit
- » Improve product quality
- » Improve raw to finished goods

### Your Customer Benefits:

- » Product that is more tender & moist
- » Improved product appearance & better color inside
- » Consistent product quality with extended shelf life



### UltraSource Vacuum Tumbler Specifications

MODEL	49 00 05 LT-5	49 00 15 LT-15	49 00 30 LT-30	49 00 60 LT-60
All Stainless steel construction with USDA	Standard	Standard	Standard	Standard
Length	32-in.	47-in.	52-in.	76-in.
Width	20-in.	27-in.	31-in.	31-in.
Height	21-in.	35-in.	49-in.	49-in.
Capacity Pounds	40	150	400	800
Vacuum Pump System				
Maximum Vacuum (liquid trap)	26-in.	26-in.	26-in.	26-in.
Variable Speed Drive	1-20 rpm	1-9 rpm	1-9 rpm	1-9 rpm
Tumble Timer	80-min option	8-hour	8-hour	8-hour
Delay Start	N/A	Optional	Optional	Optional
Intermittent On	N/A	Optional	Optional	Optional
Intermittent Off	N/A	Optional	Optional	Optional
Total Time	N/A	Optional	Optional	Optional
115 Volt, 60 Hertz, Single Phase				
Variable, Speed Motor	1.8 amps	5.0 amps	6.2 amps	11.0 amps
Vacuum Pump Motor	2.0 amps	2.0 amps	9.4 amps	9.4 amps
Shipping Weight (Class 92.5)	100-lbs	400-lbs	650-lbs	750-lbs
Door Opening	-	12.5in x 23.75in	12.5in x 23.75in	12.5in x 23.75in